AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

- 1. (currently amended) A wireless communication system comprising multiple terminals each of which terminals has an a unique terminal identifier to be identified from any other terminal on the network, wherein each respective of said multiple terminals provides comprises:
- a terminal identification means for identifying any other terminal with which an individual the respective one of the terminal itself terminals communicates using the terminal identifier of another the other terminal;
- a duplication notification means that operates when that individual the respective terminal detects the existence of another terminal having the same terminal identifier as itself the respective terminal to issue notification of that duplication of terminal identifiers to said other the another terminal;
- a substitute notification means which operates when said individual the respective terminal detects multiple of that plural other terminals to which said individual the respective terminal can communicate have the same terminal identifier, but differ different from the terminal identifier of said individual the respective terminal, to notify the duplication of the same

terminal identifier to all, some or at least one of said plural other terminals,

wherein said terminal identification means provides an address coordination table that, for a specified time, holds the coordination between the IP address of each other terminal on said IP network and a physical identifier unique to each said other terminal and provides a registration means that operates when a sender and IP address of a duplication notification packet received by the respective terminal from any other terminal is different from the IP address of the respective terminal, moreover said sender IP address is not registered in said address coordination table, to register said sender IP address and the physical identifier of the terminal that is said sender in said address coordination table.

- 2. (currently amended) A The wireless communication system according to claim 1 wherein each of said multiple terminals provides further comprises:
- a selection means for selecting at random a terminal identifier when commencing participation on the network;
- an inquiry means for inquiring whether or not said selected terminal identifier is duplicated with a terminal identifier being used by any other terminal that has already commenced communicating on the network;
- a means for repeating a terminal identifier selection through said selection means and/or an inquiry through said

inquiry means until discontinuation of a duplication notification from the duplication notification means or the means for issuing notification instead of another terminal on the network.

3. (currently amended) A The wireless communication system according to claim 2 wherein the network on which said multiple terminals are connected is an IP (Internet Protocol) network utilizing IP addresses for terminal identifiers and wherein:

said inquiry means includes a means for broadcasting notification in the form of a duplication inspection packet recording the IP address of said individual the respective terminal and a unique physical identifier for that individual the respective terminal to another terminal or terminals on the network;

said terminal identification means provides an address coordination—table—that, for a specified—time, holds—the coordination—between the IP address of each other terminal—on said—IP network—and—a physical—identifier—unique—to—each—said other terminal—and—provides—a registration means that operates when a sender and IP address of a duplication—notification—packet received by said—individual—terminal—from—any—other terminal—is different—to—the—IP—address—of—said—individual—terminal—itself, moreover—said—sender—IP—address—is—not registered—in—said—address—coordination—table, to—register—said—sender—IP—address—and—the

physical identifier of the terminal that is said sender in said address coordination table;

said duplication notification means includes a means for immediately sending a duplication notification packet when the sender IP address of a duplication notification packet received from another terminal by said—individual the respective terminal is the same as the IP address being used by said—individual the respective terminal itself;

said substitute notification means includes a means for sending a duplication notification packet when the sender IP address of a duplication notification packet received from another terminal is different from the corresponding physical identifier registered in said address coordination table, moreover for a specified period of time, other terminals have not sent a duplication notification packet.

- 4. (currently amended) A The wireless communication system according to claim 3 wherein a duplication notification packet is sent to the physical identifier of the sender of a duplication inspection packet.
- 5. (currently amended) $\frac{A}{A}$ The wireless communication system according to claim 3 wherein:
- a duplication notification packet is notified by broadcast the terminal that sent a duplication inspection packet knows of an IP address duplication through the physical identifier set in a duplication notification packet.

6. (currently amended) A The wireless communication system according to claim 2 wherein each of said individual multiple terminals provides further comprises:

an advertizing means for periodically advertizing the terminal identifier being used by an individual the respective terminal itself to the other terminals on the network after each said individual the respective terminal commences participating on the network; and

a means for changing the <u>a</u> physical identifier for that individual the respective terminal itself when the same terminal identifier that said individual the respective terminal is using or is going to use is advertized from another terminal.

- 7. (currently amended) A The wireless communication system according to claim 6 wherein each of said individual multiple terminals provides further comprises a notification means that operates when a terminal identifier advertized from one terminal is the same as the terminal identifier of a second terminal, which second terminal can communicate with a third individual terminal but which second terminal is hidden from and unable to communicate directly with said one terminal advertizing the terminal identifier, so that said notification means notifies the terminal identifier duplication to said hidden second terminal.
- 8. (currently amended) $\frac{1}{2}$ The wireless communication system according to claim 7 wherein the network on which said

multiple terminals are connected is an IP (Internet Protocol)
network utilizing IP addresses for terminal identifiers and
wherein:

said advertizing means includes a means for advertizing notification in the form of an advertizing packet recording the IP address of said individual the respective terminal and a unique physical identifier for that individual the respective terminal to another terminal or terminals on the network;

coordination tablet that, for a specified time, holds the coordination between the IP address of each other terminal on said IP network and a physical identifier unique to each said other terminal and provides a registration means that operates when a sender and IP address of an advertizing packet received by said individual terminal from any other terminal is different to the IP address of said individual terminal itself, moreover said sender IP address is not registered in said address coordination table, to register said sender IP address and the physical identifier of the terminal that is said sender in said address coordination table;

said substitute notification means operates such that when the sender IP address of an advertizing packet received from another terminal is different from the corresponding physical identifier registered in said address coordination table, in addition to sending a duplication notification packet to the

terminal for that registered physical identifier, provides a means for updating the appropriate corresponding physical identifier in said address coordination table to the physical identifier notified through the advertizing packet.

9. (currently amended) A wireless communication system comprising multiple terminals performing wireless communication each of which terminals is allocated at random a terminal identifier to identify an-individual a respective terminal itself from any other terminal on the network, wherein each respective of said multiple terminals provides comprises:

a terminal identification means for identifying any other terminal with which an individual the respective terminal itself communicates using the terminal identifier of another terminal when that individual the respective terminal performs communication with that other terminal;

an advertizing means for periodically advertizing the terminal identifier being used by that individual the respective terminal itself to the other terminals on the network after each of said individual terminal multiple terminals commences participating on the network; and

a means for changing the <u>a</u> physical identifier for that individual the respective terminal itself when the same terminal identifier that said individual the respective terminal is using or is going to use is advertized from another terminal,

said terminal identification means provides an address coordination table that, for a specified time, holds the coordination between the IP address of each other terminal on said IP network and a physical identifier unique to each said other terminal and provides a registration means that operates when a sender and IP address of a duplication notification packet received by the respective terminal from any other terminal is different from the IP address of the respective terminal, moreover said sender IP address is not registered in said address coordination table, to register said sender IP address and the physical identifier of the terminal that is said sender in said address coordination table.